

TARPAULINS • B7000

LIST OF PROPERTIES		B7000
MATERIAL COMPOSITION		
FABRIC		100 % PES / 1100 DTEX
TOTAL WEIGHT	DIN EN ISO 2286/2 1998	550 G/M ²
LACQUERING		-/-
EMBOSSING		DULL
BREAKING STRENGTH WARP	EN ISO 1421/1 1998	2500 N / 5 CM
BREAKING STRENGTH WEFT	EN ISO 1421/1 1998	1800 N / 5 CM
TEAR STRENGTH WARP	DIN 53363 2003	250 N
TEAR STRENGTH WEFT	DIN 53363 2003	250 N
ADHESION	EN ISO 2411 2000	90 N / 5 CM
TEMPERATURE RESISTANCE	DIN EN 1876/2 1998	-30/+70°C
LIGHT FASTNESS (EXCEPT WHITE AND (HALF-)TRANSPARENT)	ISO 105 B02 1988	7 - 8
FIRE BEHAVIOR	ISO 3795 1989	< 100 MM/MIN
APPLICATION		TRUCK / FLAT COVER

All our technical characteristics are indicative



1024 - 250 CM



3001 - 250 CM



5007 - 250 / 300 CM



6001 - 250 / 300 CM



7001 - 250 / 300 CM



7999 - 250 CM



9002 - 250 / 300 CM