

LIST OF PROPERTIES		C7456
MATERIAL COMPOSITION		
FABRIC		100 % PES / 1100 DTEX
TOTAL WEIGHT	DIN EN ISO 2286/2 1998	450 G/M ²
CHARACTERISTICS		ABUV
LACQUERING		1/1
EMBOSSING		LIN
BREAKING STRENGTH WARP	EN ISO 1421/1 1998	2500 N / 5 CM
BREAKING STRENGTH WEFT	EN ISO 1421/1 1998	1800 N / 5 CM
TEAR STRENGTH WARP	DIN 53363 2003	250 N
TEAR STRENGTH WEFT	DIN 53363 2003	250 N
ADHESION	EN ISO 2411 2000	70 N / 5 CM
TEMPERATURE RESISTANCE	DIN EN 1876/2 1998	-30/+70 °C
LIGHT FASTNESS (EXCEPT WHITE AND (HALF-)TRANSPARENT)	ISO 105 B02 1988	7 - 8
FIRE BEHAVIOR	ISO 3795 1989	< 100 MM/MIN
APPLICATION		CAMPING / MUDFLAP / SIDE-WALLS

All our technical characteristics are indicative.

Ⓢ THIS IS A STANDARD PRODUCT.



1617 - 150 CM



4001 - 150 CM



5041 - 150 CM



6195 - 150 CM



7005 - 150 CM



7006 - 150 CM



7007 - 150 CM



7009 - 150 CM



7211 - 150 CM



7222 - 150 CM



7999 - 150 CM



9002 - 150 CM