

TATAMI • G7655 • PHTHALATE FREE

LIST OF PROPERTIES		G7655
MATERIAL COMPOSITION		
FABRIC		100 % PES / 1 100 DTEX
TOTAL WEIGHT	DIN EN ISO 2286/2 1998	720 G/M ²
CHARACTERISTICS		1-Z / PHTHALATE FREE
LACQUERING		1/-
EMBOSSING		RICE
BREAKING STRENGTH WARP	EN ISO 1421/1 1998	2500 N / 5CM
BREAKING STRENGTH WEFT	EN ISO 1421/1 1998	1800 N / 5CM
TEAR STRENGTH WARP	DIN 53363 2003	250 N
TEAR STRENGTH WEFT	DIN 53363 2003	250 N
ADHESION	EN ISO 2411 2000	90 N / 5 CM
LIGHT FASTNESS (EXCEPT WHITE AND (HALF-)TRANSPARENT)	ISO 105 B02 1988	7 - 8
TEMPERATURE RESISTANCE	DIN EN 1876/2 1998	-30/+70°C
FIRE BEHAVIOUR	ISO 3795 1989	<100 MM/MIN
APPLICATION		SPORT & LEISURE / JUDO

All our technical characteristics are indicative.



3001 – 125 CM



6969 – 125 CM