

PLAYGROUND • B6501

LIST OF PROPERTIES		B6501
MATERIAL COMPOSITION		
FABRIC		100 % PES / 1100 DTEX
TOTAL WEIGHT	DIN EN ISO 2286/2 1998	900 G/M ²
CHARACTERISTICS		ABUV
LACQUERING		1/1
EMBOSSING		GLOSSY
BREAKING STRENGTH WARP	EN ISO 1421/1 1998	4000 N / 5 CM
BREAKING STRENGTH WEFT	EN ISO 1421/1 1998	3500 N / 5 CM
TEAR STRENGTH WARP	DIN 53363 2003	600 N
TEAR STRENGTH WEFT	DIN 53363 2003	500 N
ADHESION	EN ISO 2411 2000	100 N / 5 CM
LIGHT FASTNESS (EXCEPT WHITE AND (HALF-)TRANSPARENT)	ISO 105 B02 1988	7 - 8
TEMPERATURE RESISTANCE	DIN EN 1876/2 1998	-30/+70°C
FIRE BEHAVIOUR	ISO 3795 1989	<100 MM/MIN
APPLICATION		TOY / BOUNCY CASTLE

All our technical characteristics are indicative.



1001 - 300 CM



3015 - 300 CM



5020 - 300 CM



6037 - 300 CM