







GREASE RESISTANT - FR • B9189

LIST OF PROPERTIES		B9189
MATERIAL COMPOSITION		
FABRIC		100 % PES / 1100 DTEX
TOTAL WEIGHT	DIN EN ISO 2286/2 1998	900 G/M ²
CHARACTERISTICS		ABUV
LACQUERING		1/1
EMBOSSING		DULL
BREAKING STRENGTH WARP	EN ISO 1421/1 1998	3000 N / 5 CM
BREAKING STRENGTH WEFT	EN ISO 1421/1 1998	2800 N / 5 CM
TEAR STRENGTH WARP	DIN 53363 2003	300 N
TEAR STRENGTH WEFT	DIN 53363 2003	300 N
ADHESION	EN ISO 2411 2000	100 N / 5 CM
GAS PERMEABILITY	ISO 15105-1 / DIN 53380	< 400 CM ³ /M ² .BAR.D
TEMPERATURE RESISTANCE	DIN EN 1876/2 1998	-30/+70 °C
LIGHT FASTNESS (EXCEPT WHITE AND (HALF-)TRANSPARENT)	ISO 105 B02 1988	7 - 8
FIRE BEHAVIOR	NF P 92 507 2004	M2
FIRE BEHAVIOR	DIN 4102 1981	B1
APPLICATION		GREASE RESISTANT

All our technical characteristics are indicative

ANY COLOR – 300 CM – 1000 LM 

				
100 % PES 1100 DTEX	900 G/M ²	WA: 3000 N / 5 CM - 300 N WE: 2800 N / 5 CM - 300 N	< 400 CM ³ /M ² .BAR.D GREASE	M2 B1

 THIS IS NOT A STANDARD PRODUCT. - MIN 1000 LM