

# BOAT • D2360

D2360	LIST OF PROPERTIES
	<b>MATERIAL COMPOSITION</b>
100 % PES / 280 DTEX	<b>FABRIC</b>
360 G/M <sup>2</sup>	<b>TOTAL WEIGHT</b> DIN EN ISO 2286/2 1998
ABUV	<b>CHARACTERISTICS</b>
1/1	<b>LACQUERING</b>
BOAT	<b>EMBOSSING</b>
1300 N / 5 CM	<b>BREAKING STRENGTH WARP</b> EN ISO 1421/1 1998
1300 N / 5 CM	<b>BREAKING STRENGTH WEFT</b> EN ISO 1421/1 1998
70 N	<b>TEAR STRENGTH WARP</b> ISO 4674/1A 2004
60 N	<b>TEAR STRENGTH WEFT</b> ISO 4674/1A 2004
60 N / 5 CM	<b>ADHESION</b> EN ISO 2411 2000
-30/+70 °C	<b>TEMPERATURE RESISTANCE</b> DIN EN 1876/2 1998
7 - 8	<b>LIGHT FASTNESS (EXCEPT WHITE AND (HALF-)TRANSPARENT)</b> ISO 105 B02 1988
< 100 MM/MIN	<b>FIRE BEHAVIOR</b> ISO 3795 1989
BOATING / BOAT COVER	<b>APPLICATION</b>

All our technical characteristics are indicative

**Ⓢ THIS IS NOT A STANDARD PRODUCT. - MIN. 1000 LM.**