

LIST OF PROPERTIES	
	G7667
<b>MATERIAL COMPOSITION</b>	
<b>FABRIC</b>	100 % PES / 1100 DTEX
<b>TOTAL WEIGHT</b> DIN EN ISO 2286/2 1998	670 G/M <sup>2</sup>
<b>CHARACTERISTICS</b>	1-Z / PHTHALATE FREE / AB
<b>LACQUERING</b>	1/-
<b>EMBOSSING</b>	DP
<b>BREAKING STRENGTH WARP</b> EN ISO 1421/1 1998	2500 N / 5CM
<b>BREAKING STRENGTH WEFT</b> EN ISO 1421/1 1998	1800 N /5CM
<b>TEAR STRENGTH WARP</b> DIN 53363 2003	250 N
<b>TEAR STRENGTH WEFT</b> DIN 53363 2003	250 N
<b>ADHESION</b> EN ISO 2411 2000	90 N / 5 CM
<b>TEMPERATURE RESISTANCE</b> DIN EN 1876/2 1998	-30/+70 °C
<b>LIGHT FASTNESS (EXCEPT WHITE AND (HALF-)TRANSPARENT</b> ISO 105 B02 1988	7 - 8
<b>FIRE BEHAVIOR</b> ISO 3795 1989	< 100 MM/MIN
<b>APPLICATION</b>	GROUND SHEET / FLOORING

