

# • B7303 •

CONFORM EU DIRECTIVE  
FOR FOOD CONTACT MATERIALS



Fabric		100% PES 1100 dtex	
Total weight		550 g/m <sup>2</sup>	DIN EN ISO 2286-2
Characteristics		Foodgrade	
Lacquering		-/-	
Embossing		Dull	
Breaking strength	Warp	2500 N/5cm	EN ISO 1421-1
	Weft	1800 N/5cm	
Tear strength	Warp	250 N	DIN 53 363
	Weft	250 N	
Adhesion		90 N/5cm	EN ISO 2411
Temperature resistance		-30/+70°C	DIN EN 1876-2
Light fastness	(except white and (half-) transparent)	7-8	ISO 105 B02
Fire behavior		< 100mm/min	ISO 3795
EU Directive 2002/72/EC + amendments (direct food contact materials)		Conform	
Application	Packaging and coverage of aqueous foods having a pH > 4.5 (e.g. drinking water) and dry foods (e.g. vegetables, fruits)		

COLOR RAL WIDTH (cm)

■ 7290 - ■ S EC 1935/2004  
320

S=STANDARD - NS=This is not a standard product.  
Only on request. Minimum 1.000LM

B6303 and B7303 can be used for packaging (e.g. flexitanks) or coverage of aqueous foods having a pH > 4.5, such as drinking/ potable water, non-alcoholic beverages, dry foods such as vegetables and whole fruits.